

TECHNICAL SHEET



SUNBRELLA SOLIDS & STRIPES

Indoor and Outdoor fabrics

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100% Sunbrella solution dyed acrylic			
Weave	Canvas			ISO 7211-1
Weight	260		g/m ²	ISO 3801
Width	137		cm	EN 1773

FABRIC STRENGTH

Oil-repellent properties	5		class /8	ISO 14419
Tensile strength	160	90	daN	ISO 13934-1
Elongation at break	33	26	%	ISO 13934-1
Schmerber	200		mm	ISO 811
Spray test	5		class /5	ISO 4920
Stability on washing (40 °C)	±1	±1	%	ISO 5077
Seam slippage resistance (180 N)	3	0	mm	ISO 13936-2
Stitching strength	42.9	51.1	daN	ISO 13935-2

COLOUR RESISTANCE

Colour fastness UV indoor	8		class /8	ISO 105 B02
Colour fastness UV - outdoor	4-5		class /5	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12
Colour fastness 40°C washing	5		class /5	ISO 105 C06

USE

Roll length	50	lm	
Recommended use	Cushion, parasol and upholstery		
Guarantee*	5	Years	

*Dickson Constant guarantees Sunbrella® Indoor & Outdoor fabric's color fastness and rot-proofing for the five years following the purchase date.

Colour shades may slightly vary from dye-lot to dye-lot.



Ironing reinforces the treatment

The values for this product may have a variation of +/-5%.

